

# 1. SPECIFICATIONS

DATA U1

<b>Model name</b>		<b>CMB-P1016NU-G</b>	
<b>Number of branch</b>		16	
<b>Power source</b>		1-phase 208/230V	
		60Hz	-
<b>Power input</b>	Cooling	kW	0.217
	Heating		0.106
<b>Current</b>	Cooling	A	1.04/0.94
	Heating		0.51/0.46
<b>External finish</b>		Galvanized steel plate (Lower part drain pan :Pre-coated galvanized sheets + powder coating)	
<b>Connectable outdoor unit</b>		PURY-P72/96/108/126TGMU-A(-BS)	
<b>Indoor unit capacity connectable to 1 branch</b>	kW	Model P54 or smaller ( Use optional joint pipe combing 2 branches when the total unit capacity exceeds P55. ) ( Use the reducer (standard accessory) when the indoor unit Model 18 or smaller is connected. )	
<b>External dimension H x W x D</b>	in. (mm)	11-3/16 x 43-1/4 x 17-1/32 (284 x 1,098 x 432)	
<b>Refrigerant piping diameter</b>	<b>Connectable outdoor unit capacity</b>		<b>To outdoor unit</b>
			<b>High press. pipe</b>
			<b>Low press. pipe</b>
	P72		5/8 (15.88)
	in. (mm) O.D.		Brazed
	P96/ P108		3/4 (19.05)
in. (mm) O.D.		Brazed	
P126		3/4 (19.05)	
in. (mm) O.D.		Brazed	
			<b>To indoor unit</b>
		<b>Liquid pipe</b>	<b>Gas pipe</b>
		3/8 (9.52) Flare	5/8 (15.88) Flare
	in. (mm) O.D.	(1/4 (6.35) with attached reducer used.)	(1/2 (12.7) with attached reducer used, 3/4 (19.05) and 7/8 (22.2) with optional joint pipe used.)
<b>Drain pipe</b>		VP-25	
<b>Net weight</b>	lbs (kg)	138 (62)	
<b>Accessories</b>		Drain Connection pipe(with flexible hose and insulation) Reducer	
<b>Remark</b>			
<b>Note:</b>			
1. Works not included : Installation/foundation work, electrical connection work, duct work, insulation work, power source switch, and other items are not specified in this specifications.			
2.The equipment is for R410A refrigerant.			

Ref.: Spec\_CMB-P1016NU-G