

1. SPECIFICATIONS

DATA U1

Model name			CMB-P104NU-G		CMB-P105NU-G	
Number of branch			4		5	
Power source			1-phase 208/230V			
			60Hz	-	60Hz	-
Power input	Cooling	kW	0.060	-	0.073	-
	Heating		0.027	-	0.033	-
Current	Cooling	A	0.29/0.26	-	0.35/0.32	-
	Heating		0.13/0.12	-	0.16/0.14	-
External finish			Galvanized steel plate (Lower part drain pan :Pre-coated galvanized sheets + powder coating)			
Connectable outdoor unit			PURY-P72/96/108/126TGMU-A(-BS)			
Indoor unit capacity connectable to 1 branch			Model P54 or smaller (Use optional joint pipe combing 2 branches when the total unit capacity exceeds P55.) (Use the reducer (standard accessory) when the indoor unit Model 18 or smaller is connected.)			
External dimension H x W x D		in. (mm)	11-3/16 x 25-17/32 x 17-1/32 (284 x 648 x 432)			
Refrigerant piping diameter	Connectable outdoor unit capacity		To outdoor unit			
			High press. pipe		Low press. pipe	
	P72 in. (mm) O.D.		5/8 (15.88) Brazed		3/4 (19.05) Brazed	
	P96/ P108 in. (mm) O.D.		3/4 (19.05) Brazed		7/8 (22.2) Brazed	
	P126 in. (mm) O.D.		3/4 (19.05) Brazed		1-1/8 (28.58) Brazed	
			To indoor unit			
			Liquid pipe		Gas pipe	
in. (mm) O.D.		3/8 (9.52) Flare (1/4 (6.35) with attached reducer used.)		5/8 (15.88) Flare (1/2 (12.7) with attached reducer used, 3/4 (19.05) and 7/8 (22.2) with optional joint pipe used.)		
Drain pipe			VP-25		VP-25	
Net weight		lbs (kg)	64 (29)		72 (32)	
Accessories			Drain Connection pipe(with flexible hose and insulation) Reducer		Drain Connection pipe(with flexible hose and insulation) Reducer	
Remark						
<p>Note:</p> <p>1. Works not included : Installation/foundation work, electrical connection work, duct work, insulation work, power source switch, and other items are not specified in this specifications.</p> <p>2.The equipment is for R410A refrigerant.</p>						

Ref.: Spec_CMB-P104-105NU-G